
RECORD OF SURVEY

A PORTION OF THE NORTHEAST QUARTER OF THE NORTHEAST QUARTER OF SECTION 8, TOWNSHIP 14 NORTH, RANGE 45 EAST, WILLAMETTE MERICIAN, CITY OF PULLMAN, WHITMAN COUNTY, WASHINGTON



CORNER NOTES:

- F1 Found 3 1/2" Brass Cap for North Quarter Comer marked "WHITMAN COUNTY MONUMENT, 5, 8, T14 R45, WASHINGTON LS REG NO. 14827".
- Found 3 1/2" Brass Cap for Northeost Section Corner morked "WHITMAN COUNTY MONUMENT, 5 | 4, 8 | 9, T14 R45, WASHINGTON LS REG 8996", 0.17± below surface, Southeast of white carsonite, 6' West of power pale.
- Found 3 1/2" Bross Cap for Center of Section Carner marked "WHITMAN COUNTY MONUMENT, G7, 8 T R45, WASHINGTON LS 14827 REG NO."

- WASHINGION LS 14827 REG NU.
 Found Mag Nall with 2" Washer marked "CARSTEN, PLS 45152" at surface.
 Found 5/8" Rebar with YPC marked "CARSTEN, PLS 45152" at surface.
 Found 5/8" Rebar, no cap, bent to the west 0.4'± below surface, N64'34'02"W, 0.15' from the calculated postian.
 Found 1/2" Rebar with YPC marked "A&C, 12904, at fence comer, S000'417", 0.18' from the calculated postian.
- Found 1/2" Rebar with YPC morked "A&C, 12904, ot fence carner, S00'04'17"E, 0.39' from the calculated pastion. Faund 5/8" Rebar with YPC marked "MO&A, LS 14827", 6.0'± north af fence comer, 0.2'± above surface, N75'52'03"W,
- 0.13' from the calculated postion. F10 Found 5/8" Rebar with YPC marked "MD&A, LS 14827", In cancrete callor, 0.3' abave surface, S01'23'00"E, 0.12' fram
- the calculated pastion. Found 5/8" Rebar with YPC, smashed, 4.0'± nartheast of power pole, 0.2' below surface, S87'21'21"W, 0.55' from the
- F12 Found 1/2" Rebar na cap, bent to the west, 2.0'± west of power pale, 0.3'± above surface, S87'21'21"E, 8.29' from the calculated postlan.
- F13 Found 5/8" Rebor with YPC marked "MO&A, LS 14827", 6.0' west of fence, 0.3'± above surface.
- Found 5/8" Rebar with YPC marked "LS 12896", 0.4'± below surface, N01'27'00"W, 0.137' from the colculated postion.
- F15 Found 5/8" from Pin, smooth surface, 0.2'± above surface.
- F16 Found 3/4" Rebar no cap, on fence line, 0.5'± above surface.

SURVEYOR'S CERTIFICATE:

This map carrectly represents a survey made by me or under my direction in conformance with the requirements of the Survey Recording Act at the request of Gary McVilliams in January of 2016.

Darrel Wayne Corsten, PLS 45152

AUDITOR'S CERTIFICATE:

Filed far recard this	_ Oay af			2016,	at at	Page
M. in Book 9 Auditor's File Number		at	the	reque	st (of
Whitman County Auditor						

734702 Surveys Reo Fee: \$ 162.00 8471222016 10:32 AM Pape: 1 of 2 8471222016 10:32 AM Pape: 1 of 2

OFFICIAL DOCUMENTS:

- Pioneer Title Campany, Title Order Na. P-88229, Floyd Short and Kamada Investments, LLC, January, 2016, Researched By. J. Tadd Cummlng Northern Paclfic Railroad, Right of Way And Track Mop, Idoha Olivisian, Polouse and Lewistan Branch, Pages VII-19, VII-ST&S 19A, VII-20, VII-ST&S 20A, ONR 00C 10 263743, Created in ONR 2001. Narthern Paclfic Railroad, Pullman Junction, Station Map Tracks & Strictures, Office Olstrict Engineer, Speking Washbartan 1940.
- Spokane, Washington, 1940. Spokane, Wasningtan, 1940.
 Whitman County Engineer, Map & Profile Pullman—Busby Road, C.R.P. No. 115-F.A.S.669-S.0669(1),
 Sheets 2 and 3 of 5 Sheets, by John Arrasmith, January 3, 1956.
 Gormsen Subdivisian No 1, AFN 628503, 2001, Surveyor: Daud
 SP, Gormsen Shart Plot No. 1, AFN 605259, 1997, Surveyor: Murtho
 Survey For; Komada Investment, LLC, AFN 727958, 2015, Surveyor: Carsten

- Survey ror; komada investment, LLC, ArN 72/958, 2015, Surveyor Survey For; Margle Celmer, AFN 720834, 2013, Surveyor: Carsten Survey For; Verlzon, AFN 654332, 2004, Surveyor: Clark Survey For; Greg Haynes, AFN 639525, 2002, Surveyor: Murtho Survey For; Mike Gormsen, AFN 71720, 1992, Surveyor: Murtha
- Survey For, Pullman Congregation of Jehovah's Witnesses Inc., AFN 71114, 1976, Surveyor: Carey

LAND DESCRIPTION PER RI

A tract of land in the northeast quarter of the nartheast quarter of Section 8, Tawnship 14 North, Range 45 East, W.M., described as follows:

COMMENCING at the northeast corner of said Section 8 and running thence along the section line south 4"12" west a distance of 4.33 chains (285.78 feet); thence north 87'56" west 11.13 chains (734.58 feet); thence north 1'25" east 4.11 chains (271.26 feet) to the north line of said section; thence south 89'06" east 11.33 chains (747.78 feet) to the place of BEGINNING.

LAND DESCRIPTION

DESCRIPTION of a parcel of land located in the Northeast Quarter of the Northeast Quarter of Section 8, Township 14 North, Range 45 East, Willamette Meridian, City of Pullman, County of Whitman, State of Washington, more particularly described as follows:

BEGINING AT the Northeost Camer of sold Section 8, sold camer bears North 87'14'26" East,

2662.97 feet from the North Quarter Corner of said Section 8, Thence South 00'30'04" East, 285.83 feet dang the east line of said Section 8; Thence South 87'21'21" West, 727.52 feet to the east right of woy line of Johnson Avenue and to a point an a curve to the left;

a point an a curve to the left;
Thence the following 3 courses along sold right of way line;

1) Along a non-tangent curve to the left, the radius of which bears South 84*10'35" West
1939.86 feet, a central angle of 01'23'52", (the chard of which bears North 06'31'21" West,
47.32 feet), far an arc length of 47.33 feet along said east right of way line of Johnson

2)Narth 0713'18" West, 125.03 feet to a paint on a curve to the left, on the east right of way line of the Northern Pacific Railroad;

line of the Narthern Pacific Railroad;
3)Along a nan-tangent curve to the left, the radius of which bears South 86'22'55" West
3919.72 feet, a centrol angle of 01'38'31", (the chard of which bears North 04'26'20" West,
112.32 feet), for an arc length of 112.32 feet to the north line of said Section 8;
Thence North 87'14'26" East, 754.91 feet clang said north line to the POINT OF BEGINNING.

CONTAINING: 211,520.0 square feet or 4.86 acres af land, more ar less.

SURVEYORS NOTES:

- We accepted the monuments F1 and F2 as the north line of Section 8, Township 14 North, Range 45 East, Williamette Meridian. A partian of said north line is the north boundry of the subject
- praperty.

 We accepted the manuments F2 and F16 as the east line of said Section 8. A portion of said east line is the east boundry of the subject property.

 We used a best fit line between the manuments F9, F10 and F11, and extended said line to the
- east line of said said Section 8 and trimed the line at the east right of way line of Johnson
- 4. We used R3 to reconstruct the centerline Johnson Avenue and best fit said centerline between We used NO reconstruct the centerline Station calls to the north line of sold Section 8 and the south line of the Northeast Quorter of sold Section 8. We offset sold centerline easterly 30 feet for the east right of way line of said Johnson Avenue. A portion of the east right of way is a portion of the west
- of way line of said Johnson Avenue. A portion of the east right of way is a partial of the subject property.

 5. We used R1 and R2 to reconstruct the centerline of the Northern Pacific Rollroad and best fit sold centerline with field lacates of the approximate centerline of the now remaved tracks to the centerline Station colls and the north line of said Section 8. We offset said centerline 100 feet easterly and westerly far the east and west right of way line for said railroad. A partian of the east right of way is a portion of the west boundary line of the subject property.



S.B, T.14N., R.45E.

Taylor Engineering, Inc. Civil Design and Land Planning 245 E. Main St. Pullman, Washington 99163 (509) 334-5115 FAX (509) 334-5956

DATE: 02-17-16 FIELD CREW: JUV DWN: DWC CK'D: ERC PROJ.#: 16-P008 SHEET

SURVEY FOR CROSSROADS RETAIL CENTER OF

